



# HVL 25 PUSH



## STANDARD FEATURES

- Outriggers with interlock
- AC Power to platform
- Emergency stop button
- Emergency lowering system
- Presence switch
- Cylinder holding valve
- Fits through a 36" wide doorway
- Two controller operation
- Easy loading into back of pick up truck
- Forklift pockets
- Transport tie downs

# HVL 25 PUSH



## SPECIFICATIONS

<b>Maximum Working Height</b>	32 ft.	9.75 m	<b>Wheel Base</b>	2 ft. 7 in	0.78 m
<b>Maximum Platform Height</b>	25 ft. 6 in	7.7 m	<b>Up/Down speed</b>	32/37 sec	
<b>Loading Capacity</b>	149.7 kg	330 lbs	<b>Drive tires</b>	Roulettes	
<b>Overall Length</b>	4 ft. 4 in	1.3 m	<b>Lifting motors</b>	1.5 kW	
<b>Overall Width</b>	2 ft. 4 in	0.7 m	<b>Battery</b>	12V / 80Ah	
<b>Overall Height</b>	6 ft. 5 in	1.95 m	<b>Charger</b>	12V / 15A	
<b>Platform Dimension</b>	2 ft. 1 in x 2 ft. 1 in 0.635 m x 0.635 m		<b>Weight</b>	354.3 kg	718 lbs